

898.00 EUR  
incl. 19% VAT, plus [shipping](#)



- INTEL® Broadwell I5 5200U SoC Processor
- 2 \* SO-DIMM (Dual Channel DDR3L 1333/1600MHz SDRAM)
- Support CPU Smart FAN
- Giga LAN Port \* 2
- Support 10/100M/1000M Base-TX RJ45 Ports \* 4
- Support Watch dog Technology
- Support AC 90~240V input

- Applications ■ Industrial Control System ■  
Networking Server System ■ Security Industry

|                     |                                                                                                                                                                                                                                                                  |
|---------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| • Product Dimension | • 264 (W) * 199.4 (D) * 38 (H) mm                                                                                                                                                                                                                                |
| • Product Model     | • JBC512F3EG(W)-5200-B                                                                                                                                                                                                                                           |
| • MB Model & Size   | • NF3EP-5200 / 3.5" SBC                                                                                                                                                                                                                                          |
| • BIOS              | • AMI 32MB SMT Flash ROM                                                                                                                                                                                                                                         |
| • CPU               | • INTEL® Broadwell I5 5200U                                                                                                                                                                                                                                      |
| • Memory            | • 2 * SO-DIMM (Dual Channel DDR3L 1333/1600MHz SDRAM)                                                                                                                                                                                                            |
| • Storage Space     | • 2.5" SATA Device * 1                                                                                                                                                                                                                                           |
| • Colors            | • Black                                                                                                                                                                                                                                                          |
| • Front I/O Port    | • 4 PIN AC Input * 1<br>• AC ON-OFF * 1<br>• Power LED * 1<br>• Power SW * 1<br>• USB 2.0 * 2                                                                                                                                                                    |
| • Rear I/O Port     | • USB3.0 * 4 , USB2.0 * 2<br>• HDMI * 2<br>• Giga LAN Port * 2<br>• Audio * 1<br>• WiFi Port * 2 (JBC512F3EGW-5200-B only)                                                                                                                                       |
| • POE Port          | • 10/100M/1000M Base-TX RJ45 Ports * 4<br>• Conforms to IEEE802.3af, IEEE802.3at<br>• IEEE 802.3x full-duplex flow control, per port up to 23W<br>• Provides 4 PoE injector, per port DC52.5V-0.48A-25W<br>• For Switch : Marvell 88E6176<br>• For PoE : MAX5980 |
| • Power Source      | • 150W AC to DC OP Power inside<br>• AC 90~240V input                                                                                                                                                                                                            |
| • Accessory         | • AC Cable * 1<br>• 4 Pin Terminal block con * 1<br>• User Manual * 1<br>• CD * 1<br>• Screw Package * 1                                                                                                                                                         |

|                 |                                                                                                                                                                  |
|-----------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| • Packing       | <ul style="list-style-type: none"> <li>• Net Weight■3.6KG</li> <li>• Gross Weight■4.5KG</li> <li>• Color Box Dimension■406 (W) x 148 (D) x 359 (H) mm</li> </ul> |
| • Temperature   | <ul style="list-style-type: none"> <li>• Operating within 0~50 centigrade</li> <li>• Storage within -10-70 centigrade</li> </ul>                                 |
| • Certification | <ul style="list-style-type: none"> <li>• EMC : CE , FCC</li> <li>• Safety : RoHS , ErP</li> </ul>                                                                |
| • Applications  | <ul style="list-style-type: none"> <li>• Industrial Control System</li> <li>• Networking Server System</li> <li>• Security Industry</li> </ul>                   |